

**AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) A stator for an electromagnetic pump comprising:  
a cylinder whose both end faces are respectively closed by a pair of frames;  
a movable member having a magnetic body, in which flange sections are formed at both  
axial ends and outer circumferential faces of the flange sections act as magnetic flux working  
surfaces, said movable member being accommodated in said cylinder and capable of reciprocally  
moving in the axial direction thereof;  
pump chambers being respectively formed between inner faces of the frames and both  
side faces of said movable member extended in the moving direction thereof; and  
air-core electromagnetic coils which are wound in opposite directions being fitted around  
a periphery of said cylinder,  
wherein yokes made of a magnetic material are provided to end faces of the  
electromagnetic coils to face the flange sections of the movable body;  
an outer yoke encloses outer faces of the yokes;  
a spacer made of a nonmagnetic material or an air space is provided between adjacent  
yokes, and  
wherein the movable member is reciprocally moved repeatedly moved toward one of the  
sides according to a magnitude relation between magnetic attraction forces which work to the  
movable member and are generated by magnetic circuits formed between the flange sections and  
the adjacent yokes and between the flange sections, the end yoke, the outer yoke and the adjacent  
yokes when an electric current is supplied to the electromagnetic coils with the changing of the  
current direction, and  
wherein a restoring force for returning the movable member toward a center of a stroke is  
generated by magnetic circuits formed between the movable member and the adjacent yokes  
when the movable member is located on one of the sides and the electric current to the  
electromagnetic coils is turned off.

2-10. (Canceled)